



## Shrink Disc Model N4051

d mm	dw	Transmitting Torque Nm	Axial Thrust kN	Dimensions					Tightening screws DIN 931-10.9 No. x size	Tightening torque Nm	Contact pressure N/mm <sup>2</sup>
				D mm	I mm	L mm	d1 mm	e mm			
125	95	10550	220	185	39	51	158	6	8 X M10	59	191
	100	12100	240								
	105	13800	260								
	110	14800	265								
140	120	18640	310	220	39	51	175	6	9 X M10	59	192
	125	20500	325								
	130	24000	365								
155	135	26400	390	245	39	51	192	6	11 X M10	59	212
	140	29000	410								
	135	32000	475								
165	140	35200	500	260	46	62	210	8	10 X M12	100	224
	145	38500	530								
	145	39000	535								
175	150	42400	560	275	46	62	220	8	11 X M12	100	232
	155	46000	590								
	155	46600	600								
185	160	50300	625	295	46	62	225	8	12 X M12	100	240
	165	54000	650								
	165	63000	760								
195	170	67700	795	315	56	72	237	8	15 X M12	100	233
	175	72500	825								
	175	74000	850								
200	180	79500	890	330	56	72	242	8	16 X M12	100	243
	185	84500	915								
	180	82800	920								
220	190	93500	980	345	66	84	265	9	10 X M16	250	220
	200	105000	1055								
	200	113000	1135								
240	210	127500	1210	370	66	84	290	9	12 X M16	250	243
	215	134500	1250								
	220	149000	1350								
260	230	165000	1435	395	72	92	310	10	14 X M16	250	240
	235	173000	1475								
	230	171000	1485								
280	240	189000	1570	425	84	104	333	10	16 X M16	250	218
	250	208000	1660								
	250	215000	1720								
300	260	234000	1800	460	84	104	358	10	18 X M16	250	229
	270	255000	1890								
	270	260000	1940								
320	280	284000	2030	495	84	106	378	11	20 X M16	250	239
	290	306000	2125								
	290	300000	2070								
340	300	324400	2160	535	84	106	402	11	21 X M16	250	236
	305	337000	2210								
	300	372000	2485								
350	305	385000	2540	545	100	122	413	11	16 X M20	490	230
	310	400000	2590								
	300	360000	2400								
360	310	388000	2500	555	100	122	423	11	16 X M20	490	223
	320	415000	2590								