



## Trantorque Model N280

d x D mm	Transmitting Torque Nm	Thrust kgf	Dimensions						Tightening Torque Nm
			L1 mm	L2 mm	A1 mm	A2 mm	B1 mm	B2 mm	
15 x 38.0	180	1366	38.0	19.0	32	38.0	8.0	8.0	136
16 x 38.0	198	1500	38.0	19.0	32	38.0	8.0	8.0	136
18 x 38.0	265	1835	38.0	19.0	32	38.0	8.0	8.0	136
19 x 38.0	282	2000	38.0	19.0	32	38.0	8.0	8.0	136
20 x 45.0	290	2140	47.5	21.5	38	44.5	11.0	9.5	170
22 x 45.0	315	2446	47.5	21.5	38	44.5	11.0	9.5	170
24 x 45.0	380	2752	47.5	21.5	38	44.5	11.0	9.5	170
25 x 45.0	390	2956	47.5	21.5	38	44.5	11.0	9.5	170
28 x 51.0	495	3262	57.0	25.5	46	51.0	13.0	14.5	225
30 x 51.0	580	3568	57.0	25.5	46	51.0	13.0	14.5	225
32 x 51.0	680	3874	57.0	25.5	46	51.0	13.0	14.5	225
34 x 60.5	710	4077	70.0	38.0	50	60.3	14.0	13.0	260
35 x 60.5	725	4281	70.0	38.0	50	60.3	14.0	13.0	260
36 x 60.5	750	4485	70.0	38.0	50	60.3	14.0	13.0	260
38 x 60.5	790	4791	70.0	38.0	50	60.3	14.0	13.0	260
40 x 67.0	900	5097	79.5	43.0	60	67.0	14.5	17.5	315
42 x 67.0	1000	5043	79.5	43.0	60	67.0	14.5	17.5	315
45 x 73.0	1170	5912	90.5	51.0	65	73.0	16.0	19.0	550
48 x 73.0	1356	6422	90.5	51.0	65	73.0	16.0	19.0	550
50 x 73.0	1515	6728	90.5	51.0	65	73.0	16.0	19.0	550
55 x 80.0	1650	6932	95.0	54.0	70	79.4	16.0	20.5	600
60 x 86.0	1745	7034	98.5	57.0	75	85.7	17.5	19.0	635
65 x 92.0	1830	7136	103.0	60.5	82	92.0	17.5	20.5	680
70 x 92.0	1920	7238	103.0	60.5	82	92.0	17.5	20.5	680
75 x 100.0	2000	7339	108.0	63.5	90	98.5	19.0	20.5	750